

## DVS-G106 series

### Managed Industrial 4-Port GbE + 2-Port 100/1000Base-SFP Ethernet Switches



**Rugged**  
ETHERNET



- ▶ IPv6 address suitable for larger network and neighbor discovery
- ▶ Automatic IP assignment by DHCP/BootP server for easy network construction
- ▶ DHCP relay option 82 for sending DHCP requests with clients' identities to a DHCP server
- ▶ Port-based DHCP server with IP and MAC binding makes IP maintenance much easier
- ▶ Q-in-Q double VLAN to distinguish multiple VLANs
- ▶ SNMP v1/v2c/v3 facilitates the exchange of management between network devices
- ▶ Supports EtherNet/IP and MODBUS TCP protocols that facilitates the remote management by SCADA and other industrial devices
- ▶ Proprietary ONE RING Plus and ONE CHAIN Plus high end redundancy technology, easy to build multiple ring topology, self-healing recovery time < 10ms
- ▶ STP/RSTP/MSTP for network redundancy further ensures reliability
- ▶ QoS(IEEE 802.1p) and TOS/DSCP for mission-critical applications
- ▶ IEEE 802.1Q VLAN, MAC-based VLAN, IP Subnet-based VLAN, VLAN isolation and GVRP optimize network strategy
- ▶ Enhanced network security with IEEE 802.1X, TACACS+, SSH, HTTPS and SNMP v3
- ▶ Port-isolated for special security environment
- ▶ IEEE 802.3ad port trunking in parallel to increase the link bandwidth
- ▶ SNTP (simple network time protocol) for network clock synchronization
- ▶ Broadcast/Multicast / Unknown Unicast storm control improves throughput problems
- ▶ Loopback-Detection to avoid broadcast loops, and shutdown the corresponding ports automatically
- ▶ Intelligent Access Control List (ACL)
- ▶ MAC addresses locking function per port blocks unauthorized access
- ▶ IGMP Snooping and GMVP prunes multicast traffic
- ▶ RMON groups 1,2,3,9(history, statistics, alarms and events) for enhanced flow management and analysis
- ▶ CPU utilization displays the amount of works the CPU handles
- ▶ Port mirroring for Many-to-One ports online troubleshooting
- ▶ Versatile system file updates by TFTP, HTTPS or HTTP
- ▶ DDM diagnosis function by SFP fiber module
- ▶ Auto warning by email, DI, relay, Syslog & SNMP trap
- ▶ Compatible with various industrial protocols, including EtherNet/IP, Profinet, CC-LINK IE and DNP 3.0

## Specifications

### TECHNOLOGY

#### Standard Compliance

- IEEE 802.3 10Base-T
- IEEE 802.3u 100Base-T(X) and 100Base-FX
- IEEE 802.3ab 1000Base-T
- IEEE 802.3z 1000Base-X
- IEEE 802.3x Flow Control
- IEEE 802.1D Spanning Tree Protocol
- IEEE 802.1w Rapid Spanning Tree Protocol

- IEEE 802.1s Multiple Spanning Tree Protocol
- IEEE 802.1p Class of Service, Priority Protocols
- IEEE 802.1Q VLAN Tagging
- IEEE 802.1AD VLAN Q-in-Q
- IEEE 802.1X Port Authentication
- IEEE 802.3ad LACP Aggregation
- IEEE 802.1AB Link Layer Discovery Protocol

#### Processing Type

- Store and Forward
- IEEE 802.3x Flow control in full duplex, back-pressure flow control in half duplex

## INTERFACE

### Gigabit Ethernet

#### RJ45 Ports:

- 4 10/100/1000Base-T, auto MDI/MDI-X, auto negotiation

#### SFP Ports:

- 2 100/1000Base-SFP

### Console Port

- RS-232 (Micro-USB connector)

### LEDs

#### Device:

- PWR1, PWR2, R.M/CPLG.R, C.HD/C.TL, ALARM, DI

#### Ports:

- 100/1000M(SFP port), 10/100/1000M(RJ45 port), LINK/ACT

### Digital Inputs(DI)

- 1 set
- 0~+5V is OFF
- +11V~30V is ON
- Input current 6mA Max

### Alarm Contacts(DO)

- 1 relay output
- Carry current 1A @ 24V<sub>DC</sub>

### Reset Button

- 1 set

## PERFORMANCE AND SCALABILITY

### Switching Capacity

- 24Gbps, Wired speed, Non-blocking switching fabric

### Forwarding Rate

- 35.71Mpps

### MAC Address Table

- 8K

### Packet Buffer Memory

- 4M bits

### IGMP Multicast Groups

- 256

### Max. VLANs

- 255

### Quality of Service

- 4 priority queues per port

### DHCP/BootP Server

- 1,275 IP addresses

### Jumbo Frame

- 9,600 Bytes

## MANAGEMENT

### Software

- STP/RSTP/MSTP, LACP, QoS, IGMP Snooping v1/v2/v3, IGMP Query v1/v2, GARP, GMRP, VLAN, VLAN Q-in-Q, VLAN unaware, SSH, DNS, HTTP, HTTPS, RADIUS, TACACS+, SNMP v1/v2c/v3, SNMP Traps, TFTP, RMON, LLDP, BootP Server/Client, DHCP Server/Client, DHCP L2 Relay, DHCP Relay Option 82, DHCP Option 66/67, RARP, Telnet, Syslog, SMTP, SNTP Server/Client, IPv6, MODBUS TCP, EtherNet/IP

### Security

- Port Security, HTTPS, SSH, 802.1x, TACACS+, SNMP v3

### Configuration

- Web Browser, Cisco-like Telnet CLI, USB Local Console, SNMP, MODBUS TCP, IEXplorer Utility

### MIB

- MIB II, Bridge MIB, SNMP MIB, Ether-like MIB, Q-Bridge/P-Bridge MIB, IF MIB, Traceroute MIB, TCP MIB, UDP MIB, IP MIB, RMON Group 1,2,3,9, Delta Private MIB

## POWER REQUIREMENTS

### Input Voltage

- 2 sets, 12 to 48V<sub>DC</sub> redundant terminal block input

### Input Current

- Max. 0.58A

### Overload Current Protection

- Present, Max. Input current 12A

### Reverse Polarity Protection

- Present

### Voltage Dips Protection Time

- Min. 10ms at 48 V<sub>DC</sub>

## PHYSICAL

### Housing

- IP40 metal case

### Dimensions

- 135 mm(H) x 51 mm(W) x 135 mm (D)

### Weight

- 1,020g

### Installation

- Industrial DIN-Rail and wall mounting

## ENVIRONMENTAL LIMITS

### Operating Temperature

- -40°C to 75°C (-40 °F to 167 °F )

### Storage Temperature

- -40°C to 85°C (-40 °F to 185 °F )

### Ambient Relative Humidity

- 5% to 95% (non-condensing)

## APPROVALS

### Safety

- UL 61010, IEC 62368-1

### EMI

- FCC 47 CFR Part 15 Subpart B Class A, IEC 61000-6-4, EN 55032 (CISPR 32)

### EMS [IEC 61000-6-2, EN 55024]

- IEC 61000-4-2 level 4, IEC 61000-4-3 level 3, IEC 61000-4-4 level 4, IEC 61000-4-5 level 4, IEC 61000-4-6 level 3, IEC 61000-4-8 level 4, IEC 61000-4-29

### Environmental Type Tests

#### Cold Temperature:

- IEC 60068-2-1

#### Dry Heat:

- IEC 60068-2-2

#### Humidity:

- IEC 60068-2-30

#### Shock:

- IEC 60068-2-27

#### Freefall:

- ISTA-2A

#### Vibration:

- IEC 60068-2-6

#### Hi-Pot:

- 1.5KV

## Ordering Information

Product		Port Combination			Interface		
Model Name	Operating Temperature	Combo Port 10/100/1000Base-T and 100/1000Base- SFP	100/1000Base-SFP	10/100/1000 Base-T	DI	DO (Relay)	Power Input
DVS-G106W02-2GF	-40°C to 75°C	---	2	4	1	1	2

### Optional Products

LCP Series: 100Base-FX/1000Base-X SFP Fiber Transceiver. See the LCP Series datasheets for product information.

CliQII/PMC Series: 48 V<sub>DC</sub> Industrial Power Supply

DVP/CliQ/PMC Series: 12/24 V<sub>DC</sub> Industrial Power Supply